

# TECHTRACER KIT

## TechTracer Kit TWN4 MultiTech-P LEGIC 45\*

\*previously known as TWN4 TECH TRACER KIT LEGIC 4500M



The TechTracer Kit TWN4 MultiTech LEGIC 45 was developed for the primary purpose to determine the RFID transponder technology at the customer facility by presenting the customer card and reading the result on PC.

- Configured with Tech Tracer application
- Operates at three frequencies: 125kHz, 134.2kHz and 13.56MHz
- Simultaneously reads over forty transponder technologies (HID Prox, HID iCLASS , MIFARE Classic, MIFARE DESfire, LEGIC Advant, LEGIC Prime, Sony FeliCa, NFC)
- Powerful SDK for writing applications directly to TWN4 reader
- Includes TWN4 MultiTech–P LEGIC desktop reader, sixteen transponders in eight unique technologies, desktop reader mounting options with a Snap-in holder and Mounting Bracket, and USB memory stick with SDK and documentation.

The Elatec TWN4 MultiTech RFID reader and writer was designed as the migration reader to address the numerous transponders deployed globally from low frequency (125kHz) such as HID Prox to high frequency (13.56MHz) such as HID iCLASS and LEGIC. One reader capable of reading all technologies simplifies supply chain logistics and reduces costs.

## The TWN4 Tech Tracer Kit consists of

<b>Article</b>	<b>1x T4DT-BB7BLZ-5P</b> TWN4 MultiTech-P LEGIC DT-U120-b-L 4500M Desktop, USB cable 1.2m, Black, P-Version, pre-configured with special TechTracerApp. <b>2x ART10270</b> MIFARE Classic Card (13.56MHz) <b>2x ART10274</b> MIFARE DESFire Card (13.56MHz) <b>2x ART11861</b> HITAG-S Card (125kHz) <b>2x ART12821</b> HID iCLASS 2k Card (13.56MHz) <b>2x ART15498</b> HID Prox Card (125kHz) <b>2x ART11595</b> LEGIC Prime MIM256 (13.56MHz) <b>2x ART13777</b> LEGIC Advant ATC 1024 (13.56MHz) <b>2x ART13530</b> EM4200 KeyFob (125kHz) <b>1x HKBR-B</b> Bracket Holder Kit, Black <b>1x HKSI-B</b> Snap-In Holder incl. adhesive pads, Black <b>1x USB memory stick</b> Includes drivers, sample source code, demos, datasheets and documentation.
<b>Supported Transponders</b>	<b>125kHz / 134.2kHz</b> 4100, 4102, 4200 <sup>5)</sup> , AWID, CASI-RUSCO, Cotag, FDX-B, G-Prox <sup>8)</sup> , HID Prox, HID Prox II, HID ProxKey III, HITAG 1 <sup>6)</sup> , HITAG 2 <sup>6)</sup> , HITAG S <sup>6)</sup> , Honeywell NexWatch, Indala, ioProx, Keri, Miro, Pyramid, T5557, T5567, TIRIS/HDX, TITAN (EM4050), UNIQUE <b>13.56MHz / ISO14443A</b> MIFARE Classic 1k & 4k, Mini, DESFire EV1, Plus S&X <sup>7)</sup> , Pro X <sup>7)</sup> , Smart MX <sup>7)</sup> , Ultralight, Ultralight C, SLE44R35, SLE66Rxx (my-d move) <sup>7)</sup> , LEGIC Advant, LEGIC Prime, PayPass <sup>7)</sup> <b>13.56MHz / ISO14443B</b> PicoPass <sup>7)</sup> <b>13.56MHz / ISO18092 / NFC</b> NFCIP-1: Active and passive communication mode, NFC Peer-to-Peer <sup>1)</sup> NFC Forum Tag Type 2-4; Sony FeliCa <sup>6)</sup> <b>13.56MHz / ISO15693</b> EM4x35 <sup>7)</sup> , HID iCLASS (CSN and Facility Code), ICODE SLI, LEGIC Advant, M24LR16/64, Tag-it, SRF55Vxx (my-d vicinity) <sup>7)</sup> , PicoPass <sup>7)</sup>
<b>Order Code</b>	<b>T4DK-BB7BLZ-5P</b>

<sup>1)</sup> In Preparation <sup>2)</sup> On Request Only <sup>3)</sup> External Interface Required <sup>4)</sup> Target Specification <sup>5)</sup> UID Only <sup>6)</sup> Encryption Not Supported <sup>7)</sup> UID/PUPI Only, Read/Write On Request <sup>8)</sup> Hash Value Only



Parking



Badges



Locker locks



Library  
PC log-on



Access



Medical



Secure  
Printing



Gas / Electricity  
POS



Ticket POS



Fitness Studio  
Equipment



Kiosk / POS / POI



Elevator



Shop POS

## Detailed Information

Refer to document: Datasheet/SDK TWN4 MultiTech LEGIC, AppBlaster Guide, Overview List Transponder Cardreader ELATEC RFID